# Controller for Air Pistol target. User guide



The Controller for Air Pistol target drives three programs:

- Rapid Fire Pistol (10m 10-8-6-4 sec)
- Standard Pistol, 3x20 shots (10m 150-20-10-8-6 sec) and
- Pistol, 3x10 shots and Rapid Fire Pistol, turning target (10m 5x3 sec).

The controller also has a program to manually turn the target.

## **Program selection**

A set is started by turning the rotary switch to correct position and by pressing the start button. Restart the controller by switching off the power.

1	Pistol, 3x10 shots, 5 minutes set	select 1
2	Rapid Fire Pistol, turning target (10m 5x3 sec)	select 2
37	Standard Pistol, 3x20 shots (10m 150-20-10 sec) - 150 second set, - 20 second set,	select 3 select 4
	<ul><li>10 second set,</li><li>8 second set,</li><li>6 second set,</li></ul>	select 5 select 6 select 7

The sets (1..7) start with a buzzer sound (Start command). The sets end with a buzzer sound (Stop command). Initially the target will show. When the program is finished, the target will show again and you can start a new set.

### **8..11** Rapid Fire Pistol (10m 10-8-6 sec)

-	10 second set,	select 8
-	8 second set,	select 9
-	6 second set,	select 10
-	4 second set,	select 11

The Rapid Fire Pistol sets (8..11) start with count-down buzzer sounds: (Attention-Three-Two-One-Start) and in the end of the set a buzzer sound (Stop). Finally, after the set, the targets will show and you can start a new set.

## Controller for Air Pistol target. User guide

Running Rapid Fire Pistol, you'll need 4 more slave targets. Use the singe target unit as a master to turn the slave targets, or use the turning master target as the leftmost (last shot) target and place still standing targets as the first four targets.

#### 12/0 Manual turn

Select program 12 (or 0) and press start button to turn the target. On each button press the target will change its position. Use this program when fine tuning target positions.

#### **Set-up programs**

The adjusting of the target positions (show and hide) are preprogrammed when the unit is delivered. There is a dip-switch (or trimmer potentiometer that function as a switch) inside the turning unit to fine tune the positions. The show position is set by positioning the target on top of the unit. With the two switches you have four possible hide positions.

**Power source** Use a 9VDC or 12VDC/500mA adapter. A shivering target indicates too low current.

**Mechanics for Rapid Fire Pistol** 



Target turning units for five (picture) and single targets are available. Target turning units can be chained and operated with a single controller.

Contact: Wille Suurla, +358 40 5004119, controller, eMail: Wille@Suurla.com Pentti Paavilainen, +358 40 7738889, mechanics